Lubricants - Engine Oil - Passenger Car Motor Oils

Valvoline™ All-Climate™ DPF C3 5W-30

VALVOLINE All-Climate – High Quality Motor Oil for All Year-Round Usage.
One of the first multi-grade motor oils, All-Climate is specially formulated to provide optimal lubrication over a wide variety of operating temperatures and climatic conditions.

Performance levels
ACEA C3
API SN
BMW LL-04
Fiat 9.55535-S3 (petrol engines only)
MB-229.31, MB-229.51
VW 504 00/507 00

Applications

Suitable for a wide range of diesel and gasoline vehicles, provides optimal lubrication where ACEA C3 is specified. Specially developed for diesel vehicles with a Diesel Particulate Filter (DPF).

Features & Benefits

Year-round performance
All-Climate engine oils are formulated for year-round performance. Meeting industry performance levels.

Cold start performance
Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Wear protection
Strong oil film provides protection against wear under all operating conditions.

Engine cleanliness
Keeps engine clean by minimizing deposits.

Deposit control
Prevents forming of sludge and harmful deposits inside the engine.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **http://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **http://sds.valvolineglobal.com**

Typical properties

All Climate DPF C3 5W-30	
SAE Viscosity Grade	5W-30
Viscosity @ 100ºC, mm^2/s ASTM D445	11.7
Viscosity @ 40ºC, mm^2/s ASTM D445	69
Viscosity Index ASTM D2270	178
Viscosity @ –30°C, mPa.s ASTM D5293	< 6600
TBN, mg KOH/g ASTM D2896	9
Pour Point, ºC ASTM D5949	-39
Density @ 15°C, g/cm^3 ASTM D1298	0.854
Flash Point, COC, ºC ASTM D92	230

* The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 11/19/2025

™ Trademark, Valvoline Global Operations