

Lubricants - Engine Oil - Passenger Car Motor Oils

Valvoline™ SynPower™ XL-III C3 0W-30

VALVOLINE SynPower – OEM Approved Premium Grade Synthetic Engine Oil.

Formulated for ultimate performance and protection under all operating conditions, SynPower is designed to fulfil the latest standards of leading engine manufacturers.

OEM Approvals
BMW LL-04 >2019
BMW LL-19 FE
MB-Approval 229.52
MB-Approval 229.51
Porsche C30
VW 504 00/507 00
Performance levels
ACEA C3
MB-229.31

Applications

Formulated for Euro 4,5 and 6 engines with DPF technology (Diesel Particulate Filter). The product is suitable for engines with WIV system, for extra-long drain intervals up to 30.000 Km or 2 years.

Can be used in modern VW, AUDI, Seat and Skoda gasoline and diesel engines.

Features & Benefits

Ultimate protection and performance
SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Long drain interval
Formulated for excellent product stability. Long lasting performance and suitable for long drain intervals.

Engine cleanliness
Keeps engine extremely clean by minimizing deposits.

Optimized for emission control systems
Specifically designed for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst). Low SAPS formulation keeps the emission control system in optimal condition.

Excellent cold start performance
Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Wear protection
Provides ultimate protection against wear under all operating conditions.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **https://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **https://sds.valvolineglobal.com**

Typical properties

SynPower XL-III C3 Motor Oil	
SAE Viscosity Grade	0W-30
Viscosity @ 100ºC, mm^2/s ASTM D445	12.3
Viscosity @ 40ºC, mm^2/s ASTM D445	65
Viscosity Index ASTM D2270	190
Viscosity @ –35°C, mPa.s ASTM D5293	< 6200
TBN, mg KOH/g ASTM D2896	9.0
Pour Point, ºC ASTM D5949	-54
Density @ 15°C, g/cm^3 ASTM D4052	0.844
Flash Point, COC, ºC ASTM D92	230

*****The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 10/19/2026

™ Trademark, Valvoline Global Operations