Lubricants – Specialty Oils

Version: **502/06**

DuraBlend™ Chainsaw 2T

Synthetic blend motor oil for 2-stroke engines of chainsaws.

For light and heavy duty chainsaw equipment working under tough conditions.

Performance levels
API TC
JASO FD
ISO L-EGD
Husqvarna 242/346

Applications

Light and heavy chainsaw equipment working in forests and at home.

Prediluted and suitable for injector and pre-mix systems.
(Use fuel/oil mixtures as specified by the chainsaw manufacturer up to a maximum of 100:1).

Professional work in the forest.
Private and hobby work in the garden.
Fire brigades
Construction work
Demolition work

Features & Benefits

Smooth operation
Synthetic blend motor oil for smooth lubrication and quick cold start of the engine.

Wear protection
Upgraded wear protection, resists high speed revving.

Preservation
Base oils and additives protect the engine against rust and corrosion and extend the lifespan of the different engine parts.

Strong oil film
The product resists long term use and high temperatures when working in the forest.

Cold circumstances
With a pour point of -42ºC. DuraBlend Chainsaw 2T oil has no problems with cutting trees in the wintertime.

Hot circumstances
With its synthetic base oils and modern additive system, DuraBlend Chainsaw 2T has no problems with forest and garden work in the warm summertime.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS

PRODUCT INFORMATION

Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Typical properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

DuraBlend Chainsaw 2T	
SAE Viscosity Grade	Pre-mixed
Viscosity, mm^2/s @ 100 ºC. ASTM D-445	9,3
Viscosity, mm^2/s @ 40 ºC. ASTM D-445	57
Viscosity Index ASTM D-2270	144
Sulphated Ash, wt %	0,12
TBN, mg KOH/g ASTM D-2896	3,1
Pour Point, ºC ASTM D-5949	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,860
Flash Point, COC, ºC. ASTM D-92	94

This information only applies to products manufactured in the following location(s): Europe

Health & Safety
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://msds.valvoline.com**

Protect the environment
Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 502/05

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS