TITAN SYN MC SAE 10W-40

Super High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.

Description

TITAN SYN MC SAE 10W-40 is an advanced, SAE 10W-40 all-season, fuel economy engine oil specially formulated for gasoline and diesel engines independently of normally aspirated or turbo-charged in passenger car and van application. Universal application was a high priority in the development of this oil. The modern concept of TITAN SYN MC SAE 10W-40 offers high functionality.

Application

TITAN SYN MC SAE 10W-40 can be used for vehicles without extended drain intervals running on gasoline, diesel or gas (LPG, CNG). TITAN SYN MC SAE 10W-40 offers safe operation at all running conditions. TITAN SYN MC SAE 10W-40 is miscible and compatible with conventional branded engine-oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SYN MC SAE 10W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Unrestricted use in normally aspirated and turbo-charged gasoline and diesel engines.
- Very good viscosity-temperature behaviour and high shear stability ensure all-season suitability even at severe operating conditions
- Reliable cold starting and rapid oil circulation
- Very good wear protection
- Protects against sludging
- Compatible with all gaskets and shaft seals
- Hydraulic tappets always function reliably
- Fully miscible and compatible with all brand name single and multigrade engine oils
- Reduced oil consumption

Specifications

- ACEA A3/B4
- API SN

Approvals

- MB-APPROVAL 229.1
- MB-APPROVAL 229.3
- PSA B71 2300
- RENAULT RN0700/RN0710
- VW 502 00/505 00

FUCHS Recommendations

- API CF
- FIAT 9.55535-D2/G2

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU
Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com

TS 16949 Automotive Quality Management · AS/EN 9100 Series Aerospace · ISO 9001 Quality Management · OHSAS 18001 Occupational Health and Safety Management · ISO 14001 Environmental Management · ISO 50001 Energy Management
TS 504287 FM 58508 FM 609812 OHS 575079 EMS 71162 ENMS 621315

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.865	g/ml
Colour	DIN ISO 2049	3.5	ASTM
Flash Point, CoC	DIN ISO 2592	234	°C
Dynamic Viscosity at - 25°C	DIN 51398	6300	mPas
Kinematic Viscosity at 40°C	DIN 51562-1	91.7	mm²/s
Kinematic Viscosity at 100°C	DIN 51562-1	14.0	mm²/s

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com

TS 16949 Automotive Quality Management | AS/EN 9100 Series Aerospace | ISO 9001 Quality Management | OHSAS 18001 Occupational Health and Safety Management | ISO 14001 Environmental Management | ISO 50001 Energy Management

TS 504287 FM 58508 FM 609812 OHS 575079 EMS 71162 ENMS 621315

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products