Lubricants – Greases

Version: **616/02**

Valvoline™ Multipurpose Moly 2

High performance heavy duty lithium grease formulated with molybdenum disulphide for heavy load applications. Provides water resistance, wear and friction control.

Valvoline Multipurpose Moly 2 is a Lithium thickened lubricating grease formulated with mineral base oil and enhanced with molybdenum disulfide to provide superior performance and protection. The product is mechanically very stable and, due to its smooth consistency, easily pumpable.

Performance levels	
DIN 51502:	KPF2K-30

Applications

Suitable for use in a wide range of applications like suspension joints, steering joints, fifth wheel, slow running bearings, open gears, machines working in damp conditions etc.

Can be used in several construction, agricultural, marine, industrial and mining applications.

Features & Benefits

Superior protection
Valvoline Multipurpose Moly 2 protects against rust and corrosion and is resistant against oxidation. The grease has a good mechanical stability so that it will not be pressed away from equipment parts.

Superior performance
The molybdenum disulphide gives the grease superior anti-friction properties and helps protecting in sliding and vibrating applications where metal-to-metal contact takes place.

Multipurpose applications
Valvoline Multipurpose Moly 2 was developed for universal lubrication of several mechanical equipment requiring a Moly grease. Especially suitable for wet conditions. This product should not be used in fast running bearings.

Severe working conditions
The product can even be used in unfavorable working conditions like canal building, swamp lumbering or on-surface mining.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS

PRODUCT INFORMATION

Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Typical properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Multipurpose Moly 2	
NLGI grade	2
Soap type	Lithium/ Molybdenum disulphide
Colour	Grey / Black
Texture	Smooth
Density @ 20°C	0,950
Application temperature °C	-30 to + 120
Dropping Point, °C	195
Oil Viscosity, mm^2/s @ 40°C	100
Oil Viscosity, mm^2/s @100°C	10,0
4-Ball Weld Load, kg	240

This information only applies to products manufactured in the following location(s): Europe

Health & Safety
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://msds.valvoline.com**

Protect the environment
Take used oil and grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 616/01

™ Trademark of Valvoline, registered in various countries © 2017

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS