Automotive Chemicals – Coolant Antifreeze

Version: **2011/15 #3**

Valvoline™ HD Extended Life -67 RTU

One product, for all trucks and buses, reduces inventory, no mis-applications.

HD Extended Life is an engine coolant for trucks, buses, road construction machines and industrial equipment, which fulfills the requirements of most leading heavy-duty engine manufacturers. The product is free of amines, borates and phosphates, which makes it friendlier to the environment. HD Extended Life Coolant protects cooling systems against frost, corrosion and overheating for at least three years, 7.000 hours or 500.000 kilometers. The product is prediluted and ready to use up to a freezing temperature of -67°C. **Do not add water.** The product is mixable with other coolants on basis of mono ethylene glycol, but that may shorten the long-life characteristics. It cannot be mixed with products on basis of Propylene Glycol.
HD Extended Life -67 RTU is a fully formulated product. The product concentration is 65%.It is not necessary to add any SCA or DCA supplements.
(SCA: Supplement Coolant Additive; DCA: Diesel Coolant Additive)

Performance levels

HD Extended Life -67 RTU
ASTM D-6210, D-3306
Caterpillar EC-1
Cummins 14603, 3666286
Detroit Diesel 7SE298
Federal Spec A-A-870A
GM 1899 M, 1825 M

HD Extended Life -67 RTU
Link Belt
TEREX
Thermo King
TMC of ATA RP-329B
TMC of ATA RP-338
SAE J 814, J 1034

Features and Benefits

Unique formula for superior long-life protection
Long-Life protection by means of a unique formulation with heavy duty corrosion inhibitors to protect all cooling system metals and anti-scaling chemistry to prevent hard water scale and deposits. Unsurpassed protection for the cooling system against winter freezing and summertime over-heating. Freezing protection down to -67ºC.

Suitable for modern and older engines
HD Extended Life -67 RTU coolant protects modern vehicles with aluminum engines as well as older vehicles with cast-iron engines against corrosion and scaling. It will extend the life-span of the cooling system. Suitable for open and closed cooling systems and aluminum engine blocks. The product is mixable with other coolants on basis of ethylene glycol, but that may shorten the long-life characteristics.

Deposit control
The formulation contains extra anti-scaling additives and corrosion inhibitors to prevent the build-up of performance limiting deposits. It can keep the cooling system working efficiently by keeping heat transfer surfaces and passages clean.

No mis-applications and lowers cost of operation
HD Extended Life -67 RTU coolant can be used for all engines with all materials. Therefore, less mistakes and less storage. It provides long term protection to the cooling system of the engine for at least three years, 7.000 hours or 500.000 kilometers which lowers cost of operation.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **http://pisheets.valvolineglobal.com**

Typical properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

HD Extended Life -67 RTU	
Ready To Use	
Appearance	Thin liquid
Colour	Red
Boiling point, ºC ASTM D-1120	135 min.*
pH 50% V/V ASTM D-1287	10,5
Density, g/cm³, @ 20°C ASTM D-1122	1,096
Hard water stability	Stable

*** Boiling Point shown using conventional 15 psi Radiator cap.**

Freezing Temperature:
Ready to use product: -67 ºC

This information only applies to products manufactured in the following location(s): Europe

Health & Safety
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://sds.valvolineglobal.com**

Protect the environment
Take used product to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 2011/15#2

™ Trademark, Valvoline Global Operations ©2024 Valvoline Global Operations

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS