Lubricants – Specialty Oils

Valvoline™ Snowmobile 2T

Premium quality motor oil. Formulated with the use of synthetic technology to provide year-round protection for 2-stroke engines of snowmobiles. Developed and tested to protect and perform under all operating conditions.

Performance levels
API TC
JASO FD
ISO L-EGD

Applications

Light and heavy duty snowmobile equipment for professional or private use.

Prediluted and suitable for injector and pre-mix systems.
(Use fuel/oil mixtures as specified by the snowmobile manufacturer.

Features & Benefits

Optimal protection and performance
Valvoline Snowmobile 2T is formulated with high quality base oils and additives to ensure optimal protection and performance under all operating conditions.

Excellent cold start performance
Synthetic components improve cold temperature performance and provide quick lubrication after a cold start up.

Wear protection
Provides ultimate protection against wear under all operating conditions.

Deposit control
Prevents deposits formation in the combustion chamber and ring sticking.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **https://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **https://sds.valvolineglobal.com**

Typical properties

Valvoline Snowmobile 2T	
SAE Viscosity Grade	Pre-mixed
Viscosity @ 100ºC, mm^2/s ASTM D445	7.2
Viscosity @ 40ºC, mm^2/s ASTM D445	39
Viscosity Index ASTM D2270	150
Sulphated Ash, wt %	0.12
TBN, mg KOH/g ASTM D2896	3.1
Pour Point, ºC ASTM D5949	-48
Density @ 15°C, g/cm^3 ASTM D4052	0.864
Flash Point, COC, ºC ASTM D92	236

*****The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 8/25/2026

™ Trademark, Valvoline Global Operations