Lubricants – Greases

Version: **615/01**

Valvoline™ Multipurpose Lithium 2

Conventional multipurpose lithium grease suitable for use in normal temperature conditions.

Valvoline Multipurpose Lithium 2 is a Lithium thickened lubricating grease formulated with mineral base oil. Mechanically stable and easily pumpable due to its smooth consistency.

Performance levels	
DIN 51502:	K2K-30
ISO 12924:	L-XC(F)CHA2

Applications

Suitable for use in normal temperature conditions and in a wide range of plain and rolling bearings.

Can be used in several industrial and automotive applications.

Features & Benefits

Good protection

Valvoline Multipurpose Lithium 2 protects against rust and corrosion and has good oxidation stability properties. The grease is mechanical stable so that it will not be pressed out of bearings.

Multipurpose applications

The product was developed for universal lubrication of several mechanical equipment. Its broad applicability facilitates the choice when a general grease is required.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS

PRODUCT INFORMATION

Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Typical properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Multipurpose Lithium 2	
NLGI grade	2
Soap type	Lithium
Colour	Brown
Texture	Smooth
Density @ 20°C.	1,00
Application temperature, ºC	-30 to + 120 (max 130)
Dropping Point, ºC	> 180
Oil Viscosity, mm^2/s @ 40ºC	110
Oil Viscosity, mm^2/s @100ºC	12,0
4-Ball Weld Load, kg	200

This information only applies to products manufactured in the following location(s): Europe

Health & Safety
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://msds.valvoline.com**

Protect the environment
Take used oil or grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark of Valvoline, registered in various countries © 2017

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS