Lubricants - Engine Oil - Motorcycle Motor Oils

Valvoline™ SynPower™ 4T 10W-40

Premium quality synthetic motor oil for four-stroke motorcycle engines. Formulated for ultimate performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Performance levels
API SN
JASO MA
JASO MA2

Applications

Four-stroke motorcycle engines where SAE 10W-40 motor oil is recommended.

Wet clutch compatible and recommended for Japanese and other motorcycles where API SN or JASO MA fluids are specified.

Can be used in high-powered motorcycles.

Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump).

Can be used for motorcycles running in cold weather conditions.

Features & Benefits

Ultimate protection & performance
SynPower 4T engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading motorcycle engine manufacturers.

Wear protection
Provides ultimate protection against wear under all operating conditions. Designed to protect high performance engines.

Engine cleanliness
Keeps engine extremely clean by minimizing deposits.

Wet clutch compatible
Optimal frictional characteristics for maximum power transfer, smooth shifting and proper protection of the wet clutch. (JASO MA2 approved).

Easy starts
Recommended for quick starting, even under very cold conditions or after long periods of engine inactivity.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **http://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **http://sds.valvolineglobal.com**

Typical properties

SynPower 4T	
SAE Viscosity Grade	10W-40
Viscosity @ 100ºC, mm^2/s ASTM D445	14.5
Viscosity @ 40ºC, mm^2/s ASTM D445	94.2
Viscosity Index ASTM D2270	160
TBN, mg KOH/g ASTM D2896	7.6
Pour Point, ºC ASTM D5949	-36
Density @ 15°C, g/cm^3 ASTM D1298	0.855
Flash Point, COC, ºC ASTM D92	217

* The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 3/30/2026

™ Trademark, Valvoline Global Operations