

Lubricants - Engine Oil - Passenger Car Motor Oils

Valvoline™ SynPower™ 10W-40

Premium quality motor oil. Formulated with the use of synthetic blend technology for ultimate performance and protection under all operating conditions. Designed to fulfill the standards of leading engine manufacturers.

Performance levels
ACEA A3/B3, A3/B4
API SM, SN/CF
FPW 9.55535/04
MB-229.3
PSA B71 2300
Renault RN 0700/0710
VW 502 00/505 00
Recommended for use where Fiat 9.55535.G2 or D2 is specified

Applications

Meets the performance requirements of passenger cars and light trucks (vans), including gasoline, diesel, and LPG engines, including American, European and Japanese vehicles.

Features & Benefits

Ultimate protection and performance
SynPower engine oil is formulated with the highest quality base oils and additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the standards of leading engine manufacturers.

Deposit control
Special additives prevent the formation of sludge and harmful deposits inside the engine.

Excellent cold start performance
Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Engine cleanliness
Keeps engine extremely clean by minimizing deposits.

Wear protection
Provides ultimate protection against wear under all operating conditions.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **https://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **https://sds.valvolineglobal.com**

Typical properties

SynPower Motor Oil	
SAE Viscosity Grade	10W-40
Viscosity @ 100ºC, mm^2/s ASTM D445	13.9
Viscosity @ 40ºC, mm^2/s ASTM D445	94
Viscosity Index ASTM D2270	150
Viscosity @ –25°C ASTM D5293	< 7000
TBN, mg KOH/g ASTM D2896	10
Pour Point, ºC ASTM D5949	-39
Density @ 15°C, g/cm^3 ASTM D4052	0.869
Flash Point, COC, ºC ASTM D92	226

*****The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 7/17/2026

™ Trademark, Valvoline Global Operations