Lubricants - Engine Oil - Passenger Car Motor Oils

Version: **081/02**

Valvoline™ SynPower™ C2 5W-30

Premium quality synthetic motor oil. Formulated for ultimate performance and protection under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Approvals & Specifications
ACEA C2
API SM, SN/CF
PSA B71 2290-2012
Renault RN0700
Meets requirements of:
Honda*
Toyota*
Recommended for use where Fiat 9.55535-S1 is specified

* check owners manual before use

Applications

Specially formulated for use in modern engines, reduces exhaust emissions and improves fuel efficiency.

Suitable for use in the Peugeot-Citroën group.

Suitable for use in Honda and Toyota models where an ACEA C2 engine oil is recommended. Check owners manual.

Suitable for other passenger cars where API SN/CF is recommended. Please consult the owners manual before use.

Features & Benefits

Ultimate protection and performance
SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Engine cleanliness
Keeps engine extremely clean by minimizing deposits.

Optimized for emission control systems
Specifically designed for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst). Low SAPS output makes the emission control system in optimal conditions.

Excellent cold start performance
Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Wear protection
Provides ultimate protection against wear under all operating conditions.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **http://pisheets.valvolineglobal.com**

Typical properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

SynPower C2 Motor Oil	
SAE Viscosity Grade	5W-30
Viscosity, mm^2/s @ 100ºC ASTM D-445	9,6
Viscosity, mm^2/s @ 40ºC ASTM D-445	54,0
Viscosity Index ASTM D-2270	165
Viscosity, mPa.s –30°C ASTM D-5293	< 6200
TBN, mg KOH/g ASTM D-2896	8,0
Pour Point, ºC ASTM D-5949	-51
Specific Gravity @ 15.6°C ASTM D-4052	0,853
Flash Point, COC, ºC ASTM D-92	227

This information only applies to products manufactured in the following location(s): Europe

Health & Safety
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://sds.valvolineglobal.com**

Protect the environment
Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 081/01

™ Trademark, Valvoline Global Operations ©2024 Valvoline Global Operations

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS