Lubricants - Engine Oil - Passenger Car Motor Oils

Valvoline™ SynPower™ FE 0W-30

VALVOLINE SynPower – OEM Approved Premium Grade Synthetic Engine Oil.
Formulated for ultimate performance and protection under all operating conditions, SynPower is designed to fulfil the latest standards of leading engine manufacturers.

OEM Approvals
BMW LL-01FE
Volvo 95200377
Performance levels
ACEA A5/B5
ACEA A7/B7
API SP
MB-229.6
Renault RN0700

Applications

SynPower FE 0W-30 has been formulated to meet Volvo 95200377 lubricant specification. FE 0W-30 is designed to maintain fuel efficiency in diesel and gasoline vehicles, where a 0W-30 is recommended.

Specially formulated for use in cars and light commercial vehicles including petrol, diesel, and LPG engines, where a 0W-30 is recommended.

For vehicles operating in cold conditions.

Always check the owner's manual for the correct oil specification to use.

Features & Benefits

Protects Engine and Emissions System
SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Engine cleanliness
Keeps engine extremely clean by minimizing deposits.

Fuel Economy
Low viscosity and special additives result in maximum reduction of friction which results in a lower fuel consumption.

Wear protection
Provides ultimate protection against wear under all operating conditions.

Excellent cold start performance
Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **https://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **https://sds.valvolineglobal.com**

Typical properties

SynPower FE	
SAE Viscosity Grade	0W-30
Viscosity @ 100ºC, mm^2/s ASTM D445	9.8
Viscosity @ 40ºC, mm^2/s ASTM D445	50
Viscosity Index ASTM D2270	185
Viscosity @ –35°C, mPa.s ASTM D5293	6061
TBN, mg KOH/g ASTM D2896	12.5
Pour Point, ºC ASTM D5949	-48
Density @ 15°C, g/cm^3 ASTM D4052	0.846
Flash Point, COC, ºC ASTM D92	224

*****The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 10/23/2026

™ Trademark, Valvoline Global Operations