*Lubricants – Hydraulic oils*

Version: **138/03RU**

# Valvoline™ HLP R 68

***Hydraulic oil formulated for industrial and earth moving equipment.***

Valvoline HLP R 68 is a hydraulic oil, formulated with high quality mineral base oils and additives to offer solid hydraulic performance in a wide range of applications.

| Performance levels |
|---|
| AIST 126 & 127 |
| ANSI/ AGMA 9005-E02-RO |
| ASTM D6158 (HM) |
| Bosch Rexroth RE 90220 |
| DIN 51524-2 (HM) |
| Eaton M-2950-S & I-286-S3 |
| GM LS-2 |
| ISO 11158 (HM) |
| MAG P69 (HM) |
| Parker (formerly Denison) HF-0, 1, 2 (HM) |
| SAE MS 1004 (HM) |
| SEB 181222 |

## Applications

For mobile and static hydraulic applications of industrial and other equipment.

Hydraulic cranes and lifts, loaders, reach trucks, forklifts, excavators, dumpers, loading ramps, and tailboards.

Sometimes recommended for: hydraulic systems of metalworking machines, or circulation systems of industrial machinery.

## Features & Benefits

### Solid performance

Formulated with high quality mineral base oils and specific additives to protect against corrosion, foaming and sludge forming.

The product can handle small quantities of penetrating dust and resists foaming, caused by access of air via leaking seals.

The product also protects the hydraulic system against rust and corrosion when working in a moist environment.

### Consistent viscosity

The product stays in grade during use and shows good viscosity-temperature behavior. Available in three ISO viscosity grades.



VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS

# PRODUCT INFORMATION

**Keeping the world moving since 1866™**
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

**Typical properties**
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

| **Valvoline HLP R 68** | |
|---|---|
| **Colour**, ASTM D-1500 | L1,5 |
| **Viscosity**, $mm^2/s$ @ 100 ºC. ASTM D-445 | 8,7 |
| **Viscosity**, $mm^2/s$ @ 40 ºC. ASTM D-445 | 68 |
| **Viscosity Index** ASTM D-2270 | >95 |
| **TAN; mg KOH/g** ASTM D-664 | <1,0 |
| **Pour Point, ºC** ASTM D-5949 | -24 |
| **Specific Gravity** @ 15.6°C. ASTM D-4052 | 0,881 |
| **Flash Point**, COC, ºC. ASTM D-92 | >195 |

**This information only applies to products manufactured in the following location(s): Russia**

**Health & Safety**
This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet **http://sds.valvoline.com**

**Protect the environment**
Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

**Storage**
We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark of Valvoline, registered in various countries © 2019

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.



VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS