Lubricants – Specialty Oils

Valvoline™ Super Outboard 2T

Premium motor oil for 2-stroke outboard engines.

Valvoline Super Outboard 2T is a high performance, ashless, 2-cycle outboard motor oil for all air and water cooled engines. This oil gives excellent lubrication and helps prevent deposits from forming in the combustion chamber. Valvoline Super Outboard 2T is pre-diluted for easier mixing and suitable for oil-injection systems. Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 100:1.

Performance levels
NMMA TC-W3
Recertified RL-56669E

Applications

Light and heavy duty outboard engines for professional or private use.

Prediluted and suitable for injector and pre-mix systems. Use fuel/oil mixtures as specified by the engine manufacturer.

Professional work on the water
Fishing boats
Maintenance boats
Rescue teams
Transportation.
Leisure.

Features & Benefits

Smooth operation
Premium motor oil for smooth lubrication and quick cold start of the engine.

Wear protection
Good wear protection resists high speed revving.

Preservation
Basic oils and additives protect the engine against rust and corrosion and extend the lifespan of the different engine parts.

Strong oil film
The product resists long term use and high engine temperatures when performing professional work on the water.

Cold circumstances
With a pour point of -42ºC Super Outboard 2T has no problems with fishing trips in the wintertime.

™ Trademark, Valvoline Global Operations



Keeping the world moving since 1866™
Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **https://www.valvolineglobal.com/en-eur/** or **https://pisheets.valvolineglobal.com**

Health & Safety
For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at **https://sds.valvolineglobal.com**

Typical properties

Super Outboard 2T	
SAE Viscosity Grade	Pre-mixed
Colour	green
Viscosity @ 100ºC, mm^2/s ASTM D445	8.5
Viscosity @ 40ºC, mm^2/s ASTM D445	51
Viscosity Index ASTM D2270	142
TBN, mg KOH/g ASTM D2896	10.5
Pour Point, ºC ASTM D5949	-42
Density @ 15°C, g/cm^3 ASTM D4052	0.872
Flash Point, COC, ºC ASTM D92	101

*****The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 8/26/2026

™ Trademark, Valvoline Global Operations